



The Profit air pressure maintenance device is a practical assembly used for regulating the air system pressure for Profit dry pipe valves type DGACV & DFACV (all sizes).

Characteristics

- Indoor use only.
- Weight: 2,4 kg.

Working pressure

0,10 to 0,17 MPa / 1,0 to 1,7 bar / 15 to 24 psi.

Assembly components

- Air regulator ¼" with pressure gauge (0,40 MPa / 4,0 bar / 60 psi max).
- ¼" Ball valve with restriction orifice, for slow fill.
- ½" Ball valve for rapid fill.
- Brass check valve ½".
- Brass strainer ½".
- Malleable fittings.

GENERAL INFO

- Installers should be trained or experienced to install and understand the product.
- Read and understand all technical datasheets and installation instructions before attempting to install, remove or adjust any Profit piping products.
- Depressurise and drain the sprinkler installation system before attempting to install, remove or adjust any Profit piping products.
- Never work on piping systems that are pressurised and / or filled with water.
- Piping Logistics reserves the right to change specifications, designs and / or standard equipment without notice and without incurring in any obligations.
- Use the necessary Personal Protection Equipment (PPE) to avoid personal injury (helmet, safety shoes and goggles, Profit gloves).



Failure to follow these instructions could result in death or serious injury and property damage.

We advise to always store our products in closed and dry environments, the products do not need any specific maintenance once installed on an aboveground sprinkler installation.

REVISION TABLE

| Date | △ | Notes |
|------------|---|-----------------|
| 07/02/2024 | | Initial release |
| | | |