



The best way to lubricate your coupling gaskets is by using Profit lubricant. Prolube xtreme is a high-end pure silicon oil lubricant, specially formulated to enable an easy and fast application in the most extreme conditions.

Applications

- Designed to prevent pinching of rubber self-sealing gaskets in couplings combined to connect grooved pipes, Profit fittings and Profit valves, including in HVAC-installations.
- Can also be used for lubricating O-ring gaskets.
- Application temperature range: -40°C up to +200°C.
- Can be applied on EPDM and NBR rubber gaskets.
- Meets German TZW/UBA & Danish (Godkendelse 06/00005) requirements for use in drinking water installations.
- Guidance:
 - Ensure that the pipe and the coupling gasket are free of dust, dirt and debris prior to application.
 - Apply by means of a brush, sponge or swab. We advise to always use Profit safety gloves.
 - Apply the lubricant on inside and outside of the gasket and/or on the outside of the pipes or fittings in the groove-sealing area.
 - Note: this lubricant is available in a 900 gr container.

Technical properties

- Colour: transparent-white.
- Consistency: pasta
- Moisture-repellent, insoluble in water
- Thixotropic

Storage

- Recommended storage temperature range: -5°C to +30°C.
- Keep separate from foods, fertilisers and/or other sensitive materials.
- Keep containers shut and out of direct sunlight, when not in use.
- Respect the expiration date. The product life is minimum 5 years after production date.

Safety information

- Page 2 + we refer to our separate document 'Safety Data Sheet', available on request.

First Aid Measures

	Description
General information	In the case of accident: contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or any other drink.
Inhalation	Bring the person into fresh air and stay with him / her.
Skin contact	Immediately remove contaminated clothing and shoes. Ensure that skin, which has been exposed to the material, is washed thoroughly with soap and water. Skin cleanser can be used. DO NOT use solvents or thinners.
Eye contact	Remove contact lenses. Flush eyes immediately with plenty of water or isotonic water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure to flush under the upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.
Ingestion	Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of, or choking on vomited material.
Burns	Not applicable.

Firefighting Measures

	Description
Extinguishing media	Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Waterjets should not be used, since they can spread the fire.
Special hazards arising from the substance or mixture	Nothing special.
Advice for firefighters	No specific requirements.

Accidental release measures

	Description
Personal precautions, protective equipment and emergency procedures	No specific requirements.
Environmental precautions	No specific requirements.
Methods and material for containment and cleanup	Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

For further information about exposure control, personal protection, physical and chemical properties, toxicological information, ecological information, disposal considerations, transport information and regulatory information, please contact Piping Logistics at info@pipinglogistics.eu

GENERAL INFO

- Installers should be trained or experienced to install and understand the product.
- Read and understand all technical datasheets and installation instructions before attempting to install, remove or adjust any Profit piping products.
- Depressurise and drain the sprinkler installation system before attempting to install, remove or adjust any Profit piping products.
- Never work on piping systems that are pressurised and / or filled with water.
- Piping Logistics reserves the right to change specifications, designs and / or standard equipment without notice and without incurring in any obligations.
- Use the necessary Personal Protection Equipment (PPE) to avoid personal injury (helmet, safety shoes and goggles, Profit gloves).



Failure to follow these instructions could result in death or serious injury and property damage.

We advise to always store our products in closed and dry environments, the products do not need any specific maintenance once installed on an aboveground sprinkler installation.